

Multiband Flyaway



Flyaway Satellite Communications Terminal

The terminal is designed to provide worldwide, continuous full-duplex data communications in a compact light weight rugged flyaway package. The system is designed to provide two simultaneous carriers on two separate frequency bands per satellite capability, C and Ku-band or X and Ka-band.

WGS Ready — TODAY!

- Single Multiband feed provides simultaneous frequency band coverage in one terminal
 - Dual-band (C/Ku or X/Ka) and Quad-band (C/Ku and X/Ka) configurations available
- Low cross-pol, high-efficiency antenna systems
- Composite reflector with or without motorization kit
- Transit case mounted multi-band electronics suite
- Quad-band terminal configuration fits into 20 transit cases
- Meets DSCS, Intelsat, Eutelsat requirements
 - Certifications: Intelsat H3 (C-Band) and E1 (Ku band); Americom GS; DSCS
- Full monitor and control software suite available
- Optional Tracking system available

Continuous Full-Duplex Data Communications

Specifications				
	C-Band	X-Band	Ku-Band	Ka-Band
Receive GHz	3.40-4.20	7.25-7.75	10.95-12.75	20.20-21.20
Transmit GHz	5.85-6.65	7.90-8.40	13.70-14.50	30.00-31.00
Receive Gain	38.0 dBi	43.5 dBi	47.2 dBi	52.0 dBi
Transmit Gain	41.0 dBi	44.0 dBi	48.7 dBi	54.0 dBi
System G/T (LNA Temp)	18 dB/K (30K)	22 dB/K (45K)	25 dB/K (65K)	27.5 dB/K (120K)
EIRP (HPA Power)	61 dBW (100W)	64 dBW (100W)	67 dBW (70W)	74 dBW (100W)
Axial Ratio • Linear Polarization • Circular Polarization	C and Ku: > 30 dB C,X, and Ka: < 1.0 dB			
Wind	Operational 30 MPH, Gusts to 45 MPH Survival 60 MPH, Gusts to 75 MPH			

Your Established Partner

TeleCommunication Systems, Inc. (TCS) (NASDAQ: TSYS) is a world leader in high availability and secure mobile communication technology. TCS infrastructure forms the foundation for market leading solutions in E9-1-1, Text Messaging, commercial location and deployable wireless communications. TCS is at the forefront of new mobile cloud computing services providing wireless applications for navigation, hyper-local search, asset tracking, social applications and telematics. Millions of consumers around the world use TCS wireless apps as a fundamental part of their daily lives. Federal government agencies depend on TCS' cyber security expertise, professional services, and highly secure deployable satellite solutions for mission-critical communications. Headquartered in Annapolis, MD, TCS maintains technical, service and sales offices around the world. To learn more about emerging and innovative wireless technologies, visit www.telecomsys.com.

TeleCommunication Systems, Inc.
275 West Street
Annapolis, MD 21401 USA
Toll Free: 1.888.728.8797
Outside US: +1.410.263.7616
www.telecomsys.com

For information contact:
3311 E. Renner Road, Suite 100
Richardson, TX 75082
1.469.330.5020
multiband@telecomsys.com

Enabling Convergent Technologies® is a registered trademark of TCS. All other trademarks are the property of their respective companies. Information subject to change without notice. | NasdaqGM: TSYS | 130226

The antenna consists of a carbon fiber composite reflector and aluminum support structure. This structure is lightweight but provides an extremely stiff support with high performance under wind loading stresses. The antenna system is supplied with 2 separate feeds for worldwide operation. The C/Ku-band feed is a high performance, multi-band feed capable of operation in C and Ku band simultaneously. The feed provides 2 port Ku-band operation and 4-port C-band operation. The C-band portion can be configured for linear or circular operation by quick removal of the polarizer section. The X/Ka-band feed is a high performance multi-band feed, capable of simultaneous operation in the military X and Ka-bands. This feed provides two-port circular polarization (with an optional 4-port configuration) in X-band, and four-port circular polarization in Ka-band.

